



## SAFETY DATA SHEET

### SECTION 1 / Identification

**IDENTITY: PREMIUM BUFFING COMPOUND**

**PRODUCT CODE: E5 -S, M, B**

**Product Use:** Compound Buffing

**Manufacturer/Distributor:** Dico Products Corporation

**Address:** 200 Seward Ave  
Utica, NY 13502

**Telephone No:** 315-797-9088

**Emergency Telephone No:** 315-797-9088

**Date:** 3/11/2015

### SECTION 2: Hazard(s) Identifications

Buffing compounds as shipped do not present a hazard.

Buffing operations may cause lint and abrasives to become airborne. Proper ventilation and respirator recommended.

**Signal Word:**



**Warning**

### SECTION 3: Composition/information on ingredients

Substance:	CAS No.	%
Hydrogenated Fatty Acid	57-11-4	less than 25 %
Petrolatum	8009-03-8	less than 15%
Aluminum Oxide	1344-28-1	less than 73 %

### SECTION 4: First Aid Measures

**Ingestion:** If swallowed - seek medical attention

**Inhalation:** Move to a fresh air environment

**Eye Contact:** Flush thoroughly with water and call physician

**Skin Contact:** Remove dust from skin with warm water and soap

### SECTION 5: Firefighting measures

**Flash Point (method used):** 350° F ( CoC )

**LEL:** N/A

**Extinguishing Media:** CO<sub>2</sub> Dry Chemical

**Special Fire Fighting Instructions:** Use Air Pack - Treat as Grease Fire

**Unusual Fire and Explosion Hazards:** Dense smoke

**Flammable Limits:** No Data

**UEL:** N/A

### SECTION 6: Accidental release measures

If material is spilled or released - sweep up with broom and dispose. Follow normal clean up procedures per State and local laws - Care taken to prevent dust from becoming airborne.

### SECTION 7: Handling and Storage

Do not store near direct heat sources - Store in a cool dry area

No other precautions apply

### SECTION 8: Exposure controls/personal protection

Hazardous Guidelines:

Hazardous Component	OSHA PEL	ACGIH / TLV
Hydrogenated Fatty Acid	15 mg ./m <sup>3</sup>	5 mg ./m <sup>3</sup>
Petrolatum	15 mg ./m <sup>3</sup>	5 mg ./m <sup>3</sup>
Aluminum Oxide	15 mg ./m <sup>3</sup>	5 mg ./m <sup>3</sup>

**Special:** None

**Mechanical ( General ):** To maintain employee below permissible limits.

**Respiratory Protection:** OSHA/MOHA approved dust mask / respirator

**Gloves:** Yes

**Eye Protection:** Safety Glasses

**Other:** Long sleeve protective clothing

**SECTION 9: Physical and chemical properties****Boiling Point:** > 450°F**Vapor Pressure (mm Hg):** N/A**Vapor Density:** N/A**Solubility in Water:** Insoluble**Appearance & Odor:** Black Bar Form**Specific Gravity:** 1.9 to 2.6**Melting Point:** 140°F**Evaporation Rate:** N/A**( Butyl Acetate=1)****SECTION 10: Stability and Reactivity****Stability:** Yes**Incompatibility:** N/A**Hazardous Decomposition of By-Products:** N/A**Hazardous Polymerization:** Will not occur**Conditions to Avoid:** N/A**SECTION 11: Toxicological Information****Route(s) of Entry :**      **Inhalation:** Yes      **Skin:**      No      **Ingestion:** Yes**Health Hazards ( Acute and Chronic** Coughing and sneezing. Buffing operations may cause lint and abrasives to become airborne. Respirator and ventilation is recommended.**Effects of overexposure:** N/A**Carcinogenicity:** N/A**NTP:** N/A**IARC Monographs:** No**OSHA Regulated:** No**SECTION 12: Ecological information ( Non-Mandatory )****SECTION 13: Disposal considerations ( Non-Mandatory )****SECTION 14: Transport Information ( Non-Mandatory )****SECTION 15: Regulatory Information ( Non-Mandatory )****SECTION 16: Other Information ( Non-Mandatory )****Revision Date:** 03/11/2015**Revision Summary:****Update all sections****Revised By:** A.Battle

