



SAFETY DATA SHEET

SECTION 1 / Identification

IDENTITY: PREMIUM BUFFING COMPOUND
PRODUCT CODE: 210-V-180-E

Product Use: Compound Buffing

Manufacturer/Distributor: Divine Brothers Company
Address: 200 Seward Ave
Utica, NY 13502
Telephone No: 315-797-0470
Emergency Telephone No: 315-797-0470
Date: 4/12/2021

SECTION 2: Hazard(s) Identifications

Buffing compounds as shipped do not present a hazard.
Buffing operations may cause lint and abrasives to become airborne. Proper ventilation and respirator recommended.

Signal Word:

Warning



SECTION 3: Composition/information on ingredients

Substance:	CAS No.	%
Saturated Fatty Acids	57-11-4	less than 20%
Petrolatum	8009-03-8	less than 70%
Aluminum Oxide	1344-28-1	less than 7%
Refined Wax	64742-43-4	less than 20%
Silica	1317-95-9	less than 20%

SECTION 4: First Aid Measures

Ingestion: If swallowed - seek medical attention
Inhalation: Move to a fresh air environment
Eye Contact: Flush thoroughly with water and call physician
Skin Contact: Remove dust from skin with warm water and soap

SECTION 5: Firefighting measures

Flash Point (method used): 350° F min (CoC)
LEL: N/A
Extinguishing Media: CO₂ Dry Chemical
Special Fire Fighting Instructions: Use Air Packs -Treat as Grease Fire
Unusual Fire and Explosion Hazards: Dense Smoke
Flammable Limits: No Data
UEL: N/A

SECTION 6: Accidental release measures

If material is spilled or released - Shovel and mop up. Use normal clean up procedures per State and local laws. Care taken to avoid dust from becoming airborne.

SECTION 7: Handling and Storage

Do not store near direct heat sources - Store in cool, dry area
 Protect from freezing temperatures
 No other precautions apply

SECTION 8: Exposure controls/personal protection

Hazardous Component	OSHA PEL	ACGIH / TLV
Saturated Fatty Acids	15mg ./m ³	5mg ./m ³
Petrolatum	15mg ./m ³	5mg ./m ³
Aluminum Oxide	15mg ./m ³	5mg ./m ³
Refined Wax	15mg ./m ³	10mg ./m ³
Silica	.1mg ./m ³	.1mg ./m ³

Special: None

Mechanical (General): To maintain employee below permissible limits.

Ventilation: Local Exhaust / Fan or Open Window

Respiratory Protection: OSHA/MOHA approved dust mask / respirator

Gloves: Yes

Eye Protection: Safety Glasses

Other: Long sleeve protective clothing

SECTION 9: Physical and chemical properties

Boiling Point: > 450°F		Specific Gravity: 1.3 to 3.5
Vapor Pressure (mm Hg): N/A		Melting Point: 140°F
Vapor Density: N/A		Evaporation Rate: N/A
Solubility in Water: Water Soluble		(Butyl Acetate=1)
Appearance & Odor: Bar Form -Black		

SECTION 10: Stability and Reactivity

Stability: Yes
Incompatibility: N/A
Hazardous Decomposition of By-Products: N/A
Hazardous Polymerization: Will not occur
Conditions to Avoid: N/A

SECTION 11: Toxicological Information

Route(s) of Entry: **Inhalation:** No **Skin:** Yes **Ingestion:** Yes
Health Hazards (Acute & Chronic) - Buffing operations may cause lint and abrasives to become airborne
We recommend respirator and ventilation.

Effects of overexposure: Irritation to eyes, ears, nose and throat
Carcinogenicity: N/A **NTP:** N/A
IARC Monographs: No **OSHA Regulated:** No

SECTION 12: Ecological information (Non-Mandatory)

Ecotoxicity: none

SECTION 13: Disposal considerations (Non-Mandatory)

Per State and Local Law

SECTION 14: Transport Information (Non-Mandatory)

Not regulated as dangerous goods

SECTION 15: Regulatory Information (Non-Mandatory)

None

SECTION 16: Other Information (Non-Mandatory)

Revision Date: 4/12/2021

Revision Summary: _____

Update all sections – Sections 3 & 8

Revised By: C Klossner