

# SAFETY DATA SHEET

# **SECTION 1 / Identification**

# IDENTITY: PREMIUM BUFFING COMPOUND PRODUCT CODE: 210-V-S-80

Product Use: Compound Buffing

Manufacturer/Distributor: Address:

Telephone No: Emergency Telephone No: Date: 1/11/2023 Divine Brothers Company 200 Seward Ave Utica, NY 13502 315-797-0470 315-797-0470

# SECTION 2: Hazard(s) Identifications

Buffing compounds as shipped do not present a hazard. Buffering operations may cause lint and abrasives to become airborne. Proper ventilation and respirator recommended.

Signal Word:

Warning



# **SECTION 3: Composition/information on ingredients**

Substance:	CAS No.	%
Saturated Fatty Acids	57-11-4	15% to 25%
Aluminum Oxides	1344-28-1	less than 80%
Petrolatum	1317-95-9	less than 8%

**SECTION 4: First Aid Measures** 

Ingestion:If swallowed - seek medical attentionInhalation:Move to a fresh air environmentEye Contact:Flush thoroughly with water and call physicianSkin Contact:Remove dust from skin with warm water and soap

# **SECTION 5: Firefighting measures**

Flash Point (method used): 350° F min (CoC)
LEL: N/A
Extinguishing Media: CO<sub>2</sub> Dry Chemical
Special Fire Fighting Instructions: Use Air Packs -Treat as Grease Fire
Unusual Fire and Explosion Hazards: Dense Smoke
Flammable Limits: No Data
UEL: N/A

# **SECTION 6:** Accidental release measures

If material is spilled or released - Shovel and mop up. Normal clean up procedures per

State and local laws. Care taken to avoid dust from becoming airborne.

# **SECTION 7: Handling and Storage**

Do not store near direct heat sources - Store in cool, dry area Protect from freezing temperatures No other precautions apply

# **SECTION 8: Exposure controls/personal protection**

Hazardous Component	OSHA PEL	ACGIH / TLV
Saturated Fatty Acids	15mg ./m³	5mg ./m³
Aluminum Oxides	15mg ./m³	5mg ./m³
Petrolatum	15mg ./m³	5mg ./m³

Special: None

Mechanical (General): To maintain employee below permissible limits.
Ventilation: Local Exhaust / Fan or Open Window
Respiratory Protection: OSHA/MOHA approved dust mask / respirator
Gloves: Yes
Eye Protection: Safety Glasses
Other: Long sleeve protective clothing

#### Page 2

210-V-S-80/SDS

## **SECTION 9: Physical and chemical properties**

Boiling Point:> 450°FVapor Pressure (mm Hg):N/2Vapor Density:N/2Solubility in Water:WaAppearance & Odor:Ba

N/A N/A Water Soluble Bar Form -White Specific Gravity: 1.5 to 3.5 Melting Point: 140°F Evaporation Rate: N/A ( Butyl Acetate=1)

# **SECTION 10: Stability and Reactivity**

Stability:YesIncompatibility:N/AHazardous Decomposition of By-Products:N/AHazardous Polymerization:Will not occurConditions to Avoid:N/A

# **SECTION 11: Toxological Information**

Route(s) of Entry:	Inhalation:	No	Skin:	Yes	Ingestion:	Yes	
Health Hazards (Acute & Chronic - Buffing operations may cause lint and abrasives to become airborne							
We recommend respirator	and ventilation.						

Effects of overexposure: Irritation to eyes, ears, nose and throatCarcinogenicity: N/ANTP: N/AIARC Monographs: NoOSHA Regulated: No

### **SECTION 12: Ecological information (Non-Mandatory)**

Ecotocity: none

### SECTION 13: Disposal considerations (Non-Mandatory)

Per State and Local Law

### SECTION 14: Transport Information (Non-Mandatory)

Not regulated as dangerous goods

### SECTION 15: Regulatory Information (Non-Mandatory)

None

# SECTION 16: Other Information (Non-Mandatory)

Revision Date: 01/11/2023

Revision Summary:

Update all sections - GHS / SDS compliance

**Revised By: C. Klossner** 

Page 3