



## SAFETY DATA SHEET

### SECTION 1 / Identification

**IDENTITY: PREMIUM BUFFING COMPOUND**  
**PRODUCT CODE :210-V-TW (WHITE ICE)**

**Product Use:** Compound Buffing

**Manufacturer/Distributor:** Divine Brothers Company  
**Address:** 200 Seward Ave  
Utica, NY 13502  
**Telephone No:** 315-797-0470  
**Emergency Telephone No:** 315-797-0470  
**Date:** 5/11/2015

### SECTION 2: Hazard(s) Identifications

Buffing Compounds as shipped do not present a hazard.  
Buffering operations may cause lint and abrasives to become airborne. Proper ventilation and respirator recommended.

**Signal Word:**

**Warning**



### SECTION 3: Composition/information on ingredients

Substance:	CAS No.	%
Saturated Fatty Acids	57-11-4	less than 2%
Silica	1317-95-9	less than 70%
Petrolatum	8 009-03-8	less than 35%
Limestone	1317-65-3	less than 25%

### SECTION 4: First Aid Measures

**Ingestion:** If swallowed - seek medical attention  
**Inhalation:** Move to a fresh air environment  
**Eye Contact:** Flush thoroughly with water and call physician  
**Skin Contact:** Remove dust from skin with warm water and soap

### SECTION 5: Firefighting measures

**Flash Point (method used):** 350° F min ( CoC )  
**LEL:** N/A  
**Extinguishing Media:** CO<sub>2</sub> Dry Chemical  
**Special Fire Fighting Instructions:** Use Air packs - Treat as grease fire  
**Unusual Fire and Explosion Hazards:** Dense smoke  
**Flammable Limits:** No Data  
**UEL:** N/A

### SECTION 6: Accidental release measures

If material is spilled or released - Shovel and mop up. Normal clean up procedures per State and local laws. Care taken to avoid dust from becoming airborne.

### SECTION 7: Handling and Storage

Do not store near direct heat sources - Store in cool, dry area

No other precautions apply

### SECTION 8: Exposure controls/personal protection

Hazardous Component	OSHA PEL	ACGIH / TLV
Saturated Fatty Acids	5mg ./m <sup>3</sup>	5mg ./m <sup>3</sup>
Silica	.1mg ./m <sup>3</sup>	.1mg ./m <sup>3</sup>
Petrolatum	15mg ./m <sup>3</sup>	5mg ./m <sup>3</sup>
Limestone	15mg ./m <sup>3</sup>	10mg ./m <sup>3</sup>

**Special:** None

**Mechanical ( General ):** To maintain employee below permissible limits.

**Ventilation:** Local Exhaust / Fan or Open Window

**Respiratory Protection:** OSHA/MOHA approved dust mask / respirator

**Gloves:** Yes

**Eye Protection:** Safety Glasses or Goggles

**Other:** Long sleeve protective clothing

